TBLA



Brida urbana autopurtata

Simbol : TBLA nx(2x0.6) conf ST 131

Tensiunea continua de exploatare:max 120V
Temperatura cond. in functionarea de durata: +70ºC
Temperatura minima de utilizare: -40 ºC

Izolatie: Polietilena de medie densitate

Purtatorul: Cond de otel zincat 7x4x0.28
Mantaua: PVC. Mantaua este cu rezistenta la propagarea flacarii
Rezistenta electrica in bucla a perechii de conductoare: max 66.6 Ω/km la 20ºC
Rezistenta la tensiune: 1 kV cc,1 minut, intre conductoare si 3 kV cc,1 minut la 50 Hz intre conductoare si purtator.
Rezistenta de izolatie la 20ºC trebuie sa fie de min 5000 MΩxkm
Capacitatea mutuala a conductorului de cupru : max 64 nF/km la si media capacitatii este de 55 nF/km.

Self-supporting strap

Symbol : TBLA NX(2x0.6) acc. to ST 131

Operation DC voltage: max 120V
Conductor temperature in long–run operation: +70ºC
Operational temperature min:-40 ºC

Insulation: medium density polyetilene

Carrier: Zinc plated steel 7x4x0.28
Sheath: PVC. The sheath is flame-resistant

Resistance of the twinned conductors (looped): max 66.6 Ω/km at 20ºC
Voltage resistance: 1 kV DC, 1 minute, at 50 Hz, between conductors 3 kV DC,1 minute at 50Hz between conductors and carrier.
Insulation resistance at 20ºC: min 5000 MΩ x km
Mutual conductor capacitance: max 64 nF/km; average capacitance: 55 nF/km

Tipodimensiune ***Cord size***	**Diam cond** ***Diam. of copper wire*** mm	**Gos rad izolatie,min** ***Radial thickness of insulation*** mm	**Gos rad manta,min** ***Radial thickness of sheath*** mm	**Diam ext max** ***Outer diameter max*** mm	**Masa inf** ***Mass, inf*** kg/km
1x(2x0.6)	0.6	0.3	0.5	9x5	49
2x(2x0.6)	0.6	0.3	0.5	10.5x6.5	65

Electroplast